




AutoGate

VERTICAL PIVOT LIFT GATE SYSTEMS



The FIRST UL-325 Compliant VPL!

- ◆ **GOVERNMENT**
- ◆ **COMMERCIAL**
- ◆ **RESIDENTIAL**

FEATURES...

UL 325 COMPLIANT (*certified early 2001*)

EXTENDED WARRANTY
(3 Yrs. Comm./5 Yrs. Res.)

STAND-ALONE SYSTEM

800 PHONE SERVICE

SPACE SAVING

CUSTOM DESIGN

ADAPTABLE TO ANY TERRAIN

STAND-ALONE 24 VDC GATE ACCESS CONTROL

24 VDC RESERVE POWER

BUILT-IN BATTERY MAINTAINER

10-12 SECOND OPERATION

CONTINUOUS DUTY SERVICE

RUST & CORROSION RESISTANT

LOW MAINTENANCE

BENEFITS...

Produced to strict standards which provides you with the safest operator possible.

Peace of mind with guaranteed savings.

24VDC power operated – *Battery back-up included at no additional charge.*

Free calls.

Costly real estate saved.

Increases property value.

Curbs -- railroad tracks -- contours

Continuous security & operation during power outages.

1000+ cycles from fully charged batteries
(*Less when access controls are used.*)

Economical 110 VAC power supply.
Maintains battery at peak reserve.

Prevents tailgating.

Dependable, worry-free operation in all services.

20+ years design life.
Saves costly replacement.

Requires simple preventative maintenance to keep system functioning properly.

24V VPL Gate Specifications

OPERATOR:	Meets UL 325 Specifications. <i>(Certified early 2001)</i>		
OPERATOR CONSTRUCTION:	Frame: 2" Sq., 11 Ga. (.120) Steel Tubing		
OPERATOR SIZE:	Skins: 18 Ga. Galvaneal Sheet	Mounting Pads: 304 SS	
PAINT:	Type: VPL-24	Length: 68"	Height: 51" Width: 30"
DUTY CYCLE:	Sherwin Williams Polane®. Std Colors: Black, White, Brown, Green & Gray (Custom colors available)		
POWER SUPPLY:	Continuous.		
POWER MAINTENANCE:	120VAC (15 amp) supply, 24v DC powered. (2) 12v Batteries required, NOT included.		
CONTROL CIRCUITRY:	24v Built-In Battery Maintainer "Over-Charge" protection built-in.		
CONTROL WIRING:	Solid state coated Control Board in NEMA 4x weatherproof electrical enclosure. Sealed Proximity Switches ensure weather & moisture-proof integrity (Boards tested to -40° F).		
GEAR MOTOR:	Horse Power: 1/3	Gear Type: Hardened Steel	
OPEN / CLOSING CYCLES:	Bearing Type: Ball	Gear Lube: Dextron II E ATF (Rated to -70° F)	
DELAYED CLOSING:	10 – 12 seconds.		
OBSTRUCTION SENSOR:	Adjustable from 0 – 60 seconds.		
SEC. BREACH PROTECTION:	Adjustable IRD senses obstructions opening or closing.		
REVERSING EQUIPMENT:	24v built-in System Brake when 120v or battery power is present.		
COMPATIBLE CONTROLS:	Optional Reversing/Safety Loop, Leading Reversing Edge, Infrared Reversing Beams, Siren or Optical Operated Sensors.		
GATE CONSTRUCTION:	Keypad, Card Reader, Intercom, Telephone, Wireless & Siren or Optical Operated Sensors.		
CHAIN LINK CONSTRUCTION:	2" Sq., 16 Ga. (.063) Steel Tubing 10'-16'	2" Sq., 11 Ga. (.120) Steel Tubing over 16' to 20'	
GATE LENGTHS:	2 1/2" Sq., 7Ga. (.187) Aluminum Tubing 21'-24'		
GATE HEIGHTS:	2-3/8", Sch. 40 & Sch. 20 Steel Tubing	9 Ga. Galv. Fabric from 12' up to 22'	
GATE HARDWARE:	2-3/8", Sch. 40 & Sch. 20 Aluminum Tubing	9 Ga. Alum. Fabric over 22' up to 24'	
ALUMINUM PICKET CONSTRUCTION:	10' – 24' (Consult factory for gates over 24').		
STEEL PICKET CONSTRUCTION:	4' – 8' from pad grade. Consult factory for gates over 8' high. (Gates over 8' will require special crating & freight arrangements).		
WINDBRACING:	Mounting hardware is 304 Stainless Steel		
DOUBLE GATES:	3/4" Sq. Aluminum Tubing		
SHIPPING WEIGHT:	75 mph design, 1/4" aircraft coated cable 16'-20'. Rigid masted alum over 20'.		
WARRANTY:	Control Panel can be set to accommodate 2 nd Operator or Sallie Port with another Operator (Optional Add). Typical VPL-24 Operator with 6' high x 16' long Buckeye style gate = 1,200 lbs. crated weight.		
	Res. = Five (5) Years / Comm. = Three (3) years from date of shipment on manufactured components and workmanship. Purchased components and accessories are covered under their respective warranties (See full Warranty for details).		



The AutoGate Advantage ...



20 years of access control technology

Quality products to fit every budget

- ◆ **Gated Communities**
- ◆ **Commercial**
- ◆ **Residential**
- ◆ **Marinas**
- ◆ **Mini-Storage**
- ◆ **Federal, State & Local**



VPL Gates are carefully designed to give years of safe and reliable operation!




Custom gate styles to fit every taste

Innovative designs for distinguished landscapes




AutoGate Gate Styles



100 Cornhusker




200 Barracuda




300 Chain Link




400 Catawba




500 Buckeye




600 Congress



700 Saratoga




800 Prestigious



900 Ohioan



1000 Islander



Operator Only