

STAND ALONE PRX-320

Water-Proof Proximity/Keypad Access Control

PRX-320

- Stand-alone unit is appropriate for use on gates or doors where there is need for resistance to climactic conditions.
- Powered by 12V DC supply
- Can be used on solar installations
- Has the option of using a built-in contact for doorbell enunciators.
- Use it as a keypad for some users and as a proximity card reader for others.



PRX-320

Proximity & Keypad Control

L=5.0" x W=2.75" x D=1.4"



CARX-20

Access Card Reinforced

L=3.4" x W=1.2" x H=0.1"
(ISO Standard size)



PRX320-PAD

Mounting
Adaptor Plate

L=6.0" x
W=4.0" x D=.5"
Polypropylene



PED-001

Gooseneck stand

EMX
INDUSTRIES, INC.

OPS Ontario
Parking
Systems Ltd.
Strong and Secure
Authorized Distributor

SPECIFICATIONS

Power Requirements:	12 VDC 500-800 mA
Power Consumption:	90 mA standby / 110 mA activated
Relay Contact Rating:	3A /12VDC
Power Indicator:	RED LED Bar on Constant
Key Confirmation:	Green LED On while key is depressed
Entry Confirmation:	Green LED Bar On for set time
Entry Denied:	Yellow LED flashing
Alarm condition:	Yellow LED constant
Read Range:	5 inches
Access:	Up to 2000 users by card or 8 user passwords
Programmable door lock settings	