

MiniProx® Reader

125 kHz Proximity

Mullion Mount Proximity Card Reader • 5365 (Wiegand), 5368 (Clock-and-Data)



ACCESS reliability.

Application

The MiniProx® proximity card reader's potted electronics enhance the security of the reader. The slim, attractive design is ideal for indoor or outdoor mounting.

Features

- ▶ Accepts 5 to 16 volts, meeting most voltage requirements.
- ▶ Available with Wiegand or Clock-and-Data interface.
- ▶ Allows easy upgrade from magstripe to a proximity reader; no rewiring or pulling of new cable required.
- ▶ Offers high reliability, consistent read-range and low power consumption in an easy-to-install package.
- ▶ Mounts directly onto metal with no change in read range performance.
- ▶ Provides multicolor LED, compatibility with all standard access control systems and internal or host control of LED and beeper.
- ▶ Includes multilingual installation manual.

Features

Mounting	Unobtrusive design mounts directly onto metal including door Mullions.
Hazardous Location MiniProx® Reader Mounting	Designed to mount onto a junction box included with each reader. The junction box is attached to an appropriate surface location utilizing four holes.
Audiovisual Indication	When a proximity card is presented to the reader, the red LED flashes green and the beeper sounds. The multicolor LED and beeper can also be controlled individually by the host system.
Diagnostics	On reader power-up, an internal self-test routine checks and verifies the setup configuration, determines the internal or external control of the LED and beeper, and initializes reader operation. An additional external loop-back test allows for the reader outputs and inputs to be verified without the use of additional test equipment.
Indoor/outdoor Design	Sealed in a rugged, weatherized polycarbonate enclosure designed to withstand harsh environments, providing reliable performance and a high degree of vandal resistance.
Easily Interfaced	Wiegand output model interfaces with all existing Wiegand protocol access control systems. Clock-and-Data (magnetic stripe) model interfaces with most systems that accept magnetic stripe readers.
Security	Recognizes card formats up to 85 bits, with over 137 billion unique codes.
Warranty	Lifetime warranty against defects in materials and workmanship (see complete sales policy for details).
Part Numbers	Base Part No.: 5365 Wiegand interface Base Part No.: 5368 Clock-and-Data interface Description: Tri-State LED, Internal beeper on Options: <ul style="list-style-type: none">• CLASSIC series cover in white, beige, charcoal gray, or black (or)• Designer series cover in white, wave blue, charcoal gray, or black• LED and beeper operation• custom label * Hazardous Location MiniProx® only available with terminal strip. (Please see "How to Order Guide" for a description of the options and associated part numbers.)

Hazardous Location MiniProx shown with incorporated junction box rated for use in hazardous locations.



Specifications

Typical Maximum* Read Range

ProxCard® II card - up to 5.5" (14 cm)
ISOProx® II card - up to 5" (12.7 cm)
DuoProx® II card - up to 5" (12.7 cm)
Smart ISOProx®/DuoProx® cards - up to 5" (12.7 cm)
Proximity & MIFARE® card - up to 5" (12.7 cm)
ProxCard® Plus card - up to 2" (5.1 cm)
ProxKey® II keyfob - up to 2" (5.1 cm)
MicroProx® Tag - up to 2.5" (6.4 cm)
*Depending on local installation conditions.

Dimensions:

6.0" x 1.7" x 1.0"
(15.2 x 4.3 x 2.54 cm)

Material: Polycarbonate UL 94

Power supply:

Standard MiniProx: 5-16 VDC
Haz. Loc. MiniProx: 5-16 VDC
Linear power supplies are recommended.

Current requirements:

Max Average 30 mA
Typ Peak: 75 mA

Operating temperature:

-22° to 150° F (-30° to 65° C)

Operating humidity:

0-95% relative humidity non-condensing

Weight:

With terminal strip: 3.5 oz. (99 g)
With pigtail: 3.8 oz. (108 g)
Haz. Loc. MiniProx: 3.8 oz. (108 g)

Transmit frequency: 125 kHz

Excite frequency: 125 kHz

Cable distance:

Wiegand interface: 500 feet (150 m)
Clock-and-Data interface: 50 feet (15 m)
Recommended cable is ALPHA 1295 (22 AWG) 5 conductor minimum stranded with overall shield or equivalent. Additional conductors may be required for LED or beeper control.

Environmental: IP55

Certifications:

UL294/cUL (US), FCC Certification (US), IC (Canada), CE (EU), C-tick (Australia, New Zealand), SRRC (China), MIC (Korea), NCC (Taiwan), MIC (Japan), iDA (Singapore), RoHS

Hazardous Part Only: Canada/UL 1604 Listed (with Haz. Loc. junction box only): Hazardous Locations Class I, Div. 2, Groups A,B,C,D.

© 2009 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2009

MKT-MINIPROX-DS-EN



ACCESS experience.

HID Global Offices:

Corporate North America
15370 Barranca Pkwy
Irvine, CA 92618
U.S.A.
Phone: (800) 237-7769
Phone: (949) 732-2000
Fax: (949) 732-2360

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Phone: +52 477 779 1492
Fax: +52 477 779 1493

hidglobal.com

