

SlideSmart™ CNX

The industry's smartest slide gate operator

Slide gate operator with advanced controls and communications. Perfect for commercial or community sites with high traffic flow or increased monitoring needs.



Features:



Weight and length limit:

Move gates up to 1,500 lbs and 50 ft



Programmable:

Over 70 user configurable settings to meet site specific requirements



Advanced:

Brushless DC motor technology, solid state limit sensors, and direct drive power train for superior control



Durable:

Equipped with long lasting corrosion resistant chain



UPS:

Standard battery backup to keep gates moving up to 100 cycles, with battery upgrades for up to 450 cycles



Diagnostics:

Easy system troubleshooting with onboard event log



Connected:

Bluetooth wireless connectivity for setup. HyNet™ technology for remote monitoring, management, and maintenance.



MADE
★ IN THE ★
USA

Adjustable:

Independent, field-adjustable open and close speeds

Made in USA:

Designed, tested and built with global materials



SlideSmart CNX

Residential and Commercial Applications



powered by
SmartCNX

Technical Specifications

Model	SlideSmart CNX 15
Gate Weight Max.	1,500 lb (680 kg)
Gate Length Max.	50 ft (15 m)
Pull Force	300 lb
Rate of Travel	0.75, 1 or 1.25 ft/s (23, 30 or 38 cm/s)* Open/Close speed set independently
Duty Cycle	Continuous
Horsepower	Equivalent to 1/2 hp
UPS Battery Backup Cycles**	Field configurable to fail open or secure when batteries deplete. Standard battery backup gate travel: Two 8Ah batteries. Up to 4,000 ft (1,219 m) after AC power loss. Extended battery backup gate travel: Two 35Ah batteries. Up to 16,000 ft (5,486 m) after AC power loss.
Temperature Rating	-13° TO 158° F (-25° TO 70° C)
Operating Voltage	24VDC
Input Voltage	Switch select 115V or 208-230V, 60/50 Hz
Accessory Power	24VDC at each input & SS relay (2A accumulative)
Included Accessories	30 ft (9 m) of #40 corrosion resistant roller chain, two cast steel gate mounting brackets for bolt-on or welded assembly, one Nice EPMAB through-beam photo eye with BlueBUS technology, one 5-foot premium ASO edge sensor and two 8Ah batteries for backup power
Communication	BlueBUS, USB, Ethernet, T4, RS-485, Bluetooth, OXI receiver
User Controls	SmartCNX™ Controller with 70+ configurable settings. 32 character OLED display and 7 tactile buttons, or Bluetooth smartphone interface, for programming.
Inputs	15 inputs including 5 control inputs, 2 dedicated entrapment sensor inputs, 3 user programmable inputs, a BlueBUS port, and 4 Hy5B vehicle detectors sockets. Optional SmartCNX™ I/O Expansion module for 8 additional user programmable inputs.
Relays	3 configurable user relays: Two 30VDC, 2A solid state. One 240VAC, 20A electromechanical; Optional SmartCNX I/O Expansion module for 8 additional relay outputs.
Finish	Zinc rich primer with black powder coated chassis. High impact copolymer cover.
ETL Listed (UL 325)	Usage Class I, II, III, IV*
Warranty	5 year (7 year single-family residential) w/product registration

* Speed setting cannot be configured to exceed 1 ft/s for Usage Class I and II.

** The actual number of gate cycles available from battery depends upon gate resistance to travel, cycle length, battery size, state of charge and health, ambient temperature, accessory power draw and frequency of gate cycles during power outage.

Optional Accessories - See website for complete list



Battery Backup Kit - 35Ah



Photo Eye Kits



CNX Remote Control Kit



Hy5B™ 2.0 Vehicle Detector



Module, I/O Expansion Board Kit



ASO Edge Sensors



Contact Nice | HySecurity for an operator/parts distributor near you.
phone 253-867-3700 | 800-321-9947
hysecurity.com | sales@hysecurity.com



D0941 121820